

5

TITLE OF THE INVENTION

**Concurrent Voice to Text and Sketch Processing with
Synchronized Replay**

10

INVENTORS

Renate Fruchter and Pratik Biswas

15

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of a co-pending U.S. patent application No. 09/568,090, filed 05/12/2000, now allowed, which claims priority from a provisional patent application No. 60/133,782, filed on 05/12/1999, both of which are hereby incorporated by reference.

20

FIELD OF THE INVENTION

This invention relates generally to network communication and, more particularly, to new processing modules and enhanced functionalities of a system and method for indexing, accessing, and retrieving concurrent voice, text, and sketch activity information with synchronized replay.

25

5 DESCRIPTION OF THE BACKGROUND ART

One major problem of multimedia communication is the large variation in the data amount of the transmitted audio and visual information. These discrepancies occur because visual and verbal information are typically correlated in an information exchange event. As a result, high data amount of simultaneous audio and visual information tend to exceed the transmission capacities of the communication infrastructure. For example, in a public switched telephone network (PSTN), a signal distributed between a number of users can carry only a certain amount of information within a given time period. The transmission of visual and verbal information therefore needs to be buffered to allow the transmission of more sophisticated visual information.

15 The buffering of the information is typically accomplished by independently saving audio information and/or video information. This buffering is accomplished temporally and/or permanently, at the location where the information is created and/or at a remote location. Subsequently, the correlated information is transmitted chronologically with a certain user definable parameter.

20 U.S. Pat. No. 4,656,654, issued to Dumas, discloses a PSTN-based computer-assisted graphic teleconferencing method and apparatus. In Dumas, graphics and voice can only be communicated alternately. Thus, with Dumas, it is not possible to simultaneously distribute a sketching activity with the contemporaneous explanatory verbal information. In addition, Dumas's invention is embodied in a PSTN-based network and not a distributed computer network such as the Internet.

5

U.S. Pat. No. 5,832,065, issued to Bannister et al., discloses a PSTN-based synchronous voice/data message system that allows the exchange of audio-graphic messages between specific portable communication devices via a PSTN. More specifically, Bannister et al., discloses how simultaneously generated voice and graphical information can be transmitted
10 over separate voice and data links and synchronized at a recipient's respective voice apparatus and data apparatus. Bannister et al. suggest that a user may wish to develop a sketch or drawing while discussing a matter with a party receiving a phone call.

However, Bannister et al.'s message system neither recognizes nor captures drawing
15 movements of a sketching activity. It is the result of the sketch or drawing activity that is being indiscriminately transmitted as a whole. Information related to the content and/or context of the sketching or drawing activity is ignored. The drawing movements are not captured or utilized.

20 On the other hand, Bannister et al.'s message system provides a replay function to display the content creation process of the graphical information together with the corresponding voice information based on a time stamping approach. In addition, the message system simultaneously replays the correlated verbal information. The chronological voice and data/graphics can be replayed at different speeds.

25

Unfortunately, Bannister et al.'s message system is unidirectional and chronological. It does not provide contextual information of a chronologically retrieved message. A user cannot

5 selectively access segments of the chronologically retrieved message. Nor can the user interactively access and select any voice or graphic segment thereof and replay from that segment and on. Moreover, to utilize Bannister et al.'s message system, a user is required to have or have access to a correct or compatible communication device. Otherwise, it is not possible to communicate with another person audio-graphically. Finally, Bannister et al.'s
10 invention is embodied in a PSTN-based point-to-point communication network and requires a centralized switching office or switch center. It is not implemented in a distributed computer network such as the Internet.

The Internet, especially the World Wide Web, has been becoming an increasingly important
15 communication medium in recent years. A number of software products and web pages exist to provide users with possibilities to exchange and collaborate audio/graphical information in substantially real time.

For instance, the RealityWave, Inc. of Cambridge, MA, USA, provides an Internet-based
20 software platform called VizStream® that allows three-dimensional (3D) graphics to be embedded within a web page accessible by a client user. RealityWave's VizStream® platform enables the access, visualization, and integration of industrial data, including complex 3D models, 2D drawings, and associated information for web-based collaboration and communication. With hierarchical streaming, VizStream® allows 3D graphics and
25 models to be viewed, animated, refined, and configured over a network connection.

5 Unfortunately, even though RealityWave's software provides an enhanced display technique, it is limited to prepared documents. The client user cannot spontaneously adding sketches or comments to the prepared drawing or document. There is no spontaneity and no bidirectional information exchange of information. Further, only 3D models are displayed and no additional media information like, for instance, audio, video, and graphics.

10 RealityWave and other existing web-based services and software platforms restrict the users to use predetermined graphical symbols together with written text. Visual information needs to be manually added. Sophisticated information elements within a single displayed image and/or in a chronological context are not captured. What is more, pertinent corresponding audio and/or video information is neither incorporated nor correlated.

15

Clearly, there exists a continuing need for an advanced multimedia communication system and method that enables two or more persons to easily and effectively communicate and interact with one another via a distributed computer network in substantially real time without being limited by special or specific equipments.

20

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a system and method that enables synchronous multimodal collaboration in a distributed network. Users having computers connected to the network would be able to share, exchange, and collaborate content rich
25 multimedia information, including free hand sketching activities or drawing movements, text, audio, video, CAD models, etc. This object is achieved in a computer system implemented with an innovative software application that captures and indexes each individual action on

5 the drawing surface and synchronizes it with audio/video (AV) capture and encoding through a client-server architecture. Such a computer system is hereinafter referred to as a RECALL™ system. Preferably, the RECALL™ application is written in Java, although other suitable computer programming language is possible.

10 The RECALL™ system comprises an interactive graphical user interface (GUI) having a color pallet and a “tracing paper” metaphor that enables a user or users to re-use a computer graphic or image file, e.g., a computer-assisted drawing (CAD) image, and create multiple sketches on top of the CAD image. That is, during the production phase of a RECALL™ session, users can create free hand sketches and/or handwritings without a background image
15 or import background images and annotate them. The RECALL™ system may employ software and hardware devices, e.g., a microphone, a video camera, a mouse, a digitizer board, a smart board, a multimodal pen or screen, etc. to capture multimodal interaction activity information such as the user’s facial expression, gesture, voice, and/or audio stream produced during a RECALL™ session.

20

Once the session is complete, the captured information, e.g., drawing and video/audio data, is automatically indexed and published on a web server, such as a RECALL™ Web Server, that enables distributed and synchronized playback of the drawing session and correlated audio/video clips from anywhere at anytime. Via appropriate output and display means, the
25 correlated and synchronized sketches, voice, text, and/or video are synchronously and accurately replayed to the user.

5 The rich and informative content enables the participating users to communicate the rationale and context in which their concepts, proposed changes, or questions came up. The interactivity with the content enables users to access the content part of interest and manage information overload. More specifically, with RECALL™, a user can conveniently and simply select an individual element, e.g., a sketch object or a keyword, as an index and jump
10 to that part of interest. The particular ability to accurately “recall” a session in its entirety and in great details, as well as the ability to allow users to freely recall a fragment of the session from a point of interest, afford RECALL™ technology with distinct advantages over conventional media capture technologies.

15 The RECALL™ system comprises several modules to process the captured multimedia/multimodal interaction information. In particular, an enhanced recognition module processes the audio stream captured during the session and a voice to text and sketch (V2TS) replay module enables a real-time, streamed, and synchronized replay of the session, including the drawing movements and the audio stream.

20

The recognition module recognizes words or phrases of an audio file created in a RECALL™ session and stores the recognized occurrences and corresponding times. The recognition module integrates a voice to text (V2T) engine to transform the voice to text. For more effective recognition, the V2T engine preferably has some trained user profiles for different
25 speakers. The recognition module takes as input the project name of the session and the user data. The audio file corresponding to the project is first converted to a format recognizable by the V2T engine. The V2T engine is then initialized and, upon the initialization, it starts to

5 transcribe. Every time the V2T engine identifies a recognizable phrase, it records a timestamp and the recognizable phrase in a text file. At the end of transcribing, it records the start and end of file timestamps in byte format.

The V2TS replay module comes into play in the replay where the stored data is used to
 10 display the recognized words and phrases in sync with the session and begin playing the session from the point when the corresponding keyword was spoken. To achieve synchronization, all different streams of data should be played in a manner that minimizes the discrepancy between the times at which concurrent events in each of the streams occurred. Accordingly, the V2TS replay module utilizes a conversion mechanism to convert
 15 timestamp information for all the streams into a common time base. The conversion mechanism for the transcribed data implements a particular algorithm described below.

As discussed before, the recognition module stores the session start and end timestamps in byte format for the transcribed data. According to an aspect of the invention, the session start
 20 and end times are stored in system clock format during the production phase of the session. Thus, for a recognized word/phrase, the corresponding system clock time can be found by scaling the raw byte data by a factor that is determined by the ratio of the time duration of the session in system clock and the time duration in bytes. That is,

$$\text{transcribed data timestamp} = (Tr * Ds / Dr) + Tsst$$

25 where

$$Tr = (\text{raw transcribed data timestamp} - \text{raw start time})$$

$$Ds = (\text{system clock session end time} - \text{system clock session start time})$$

5 Dr = (raw end time - raw start time)
 Tsst = system clock applet start time.

The Tsst term is later subtracted from the calculated value to obtain the common base timestamp.

10

The RECALL™ technology enables users to easily, accurately, and conveniently share their ideas and decisions with users virtually at anywhere. Multiple users at the same or different locations can exchange information added to a graphical and multimedia document essentially simultaneously. The instant invention further enables users to share detailed
15 multimedia/multimodal interaction information, especially sketches and drawing movements, and to reuse knowledge from project to project.

20

The RECALL™ technology disclosed herein captures the correlation between graphical and other multimedia/multimodal interaction information and enables a chronological, detailed
20 replay thereof. In some embodiments, a user can perform a keyword search for a session to identify all the keyword instances in that session and begin re-playing the session from the point when the corresponding selected keyword was spoken. Alternatively, a user can navigate through the session and jump to a particular part of interest by selecting individual sketch elements, as described above.

25

In addition to the aforementioned advantages, the present invention has many useful applications and offers many advantages over existing knowledge capture and interactive

5 communication technologies. For example, the present invention provides users with zero or little overhead cost for indexing and publishing on the Web rich content in the form of sketches, audio and video, as well as real time interactivity with the rich content. In terms of interaction among participating users, the present invention enables a fast turnover of information and feedback. For example, an instructor can have an insight into a learner's
10 thought process; similar benefits can be observed in play mode or in customer relation management. Since the knowledge is in context, participating users can therefore make informed decisions.

Still further objects and advantages of the present invention will become apparent to one of
15 ordinary skill in the art upon reading and understanding the detailed description of the preferred embodiments and the drawings illustrating the preferred embodiments disclosed herein.

BRIEF DESCRIPTION OF THE FIGURES

- 20 **FIG. 1** shows an example of a basic sketch entity with a single initiation event and a single termination event.
- FIG. 2** shows an example of an advanced sketch entity with multiple initiation events and multiple termination events.
- FIG. 3** shows an exemplary graph of a basic procedure to capture sketching activities and
25 associated multimodal interaction information.
- FIG. 4** shows an exemplary graph of an advanced procedure to capture sketching activities and associated multimodal interaction information.

5 **FIG. 5** shows a simplified example of an interactive graphical user interface with sketch entities that are marked and correlated to user identities.

FIG. 6 shows a simplified example of an interactive graphical user interface with sketch entities that are marked to visualize the availability of associated multimodal interaction information.

10 **FIG. 7** shows a simplified example of an interactive graphical user interface with sketch entities that are marked to visualize the chronological creation process of the sketch entities.

FIG. 8 shows design objectives of the recognition module and the V2TS replay module.

FIG. 9 is a flow diagram of the recognition module according to the present invention.

15 **FIG. 10** is a snapshot of an exemplary interactive graphical user interface with an embedded media player for synchronized audio replay, a replay frame showing a background image annotated with sketch entities, a keyword search facility, and a text replay frame showing the synchronized audio replay in text format.

FIG. 11 diagrammatically shows the V2TS replay module hierarchy.

20 **FIG. 12** diagrammatically shows the V2TS replay module control flow.

FIG. 13 is a snapshot of another exemplary interactive graphical user interface with enhanced functionalities, a color pallet, and a canvas showing an imported CAD image and sketch objects annotating the CAD image.

FIG. 14A shows a simplified centralistic distribution system architecture.

25 **FIG. 14B** shows an aspect of the simplified system architecture of **FIG. 14A**.

FIG. 15 shows a simplified equalized distribution system architecture.

5

DETAILED DESCRIPTION

Although the following detailed description contains many specifics for the purposes of illustration, anyone of ordinary skill in the art will appreciate that many variations and alterations to the following details are within the scope of the invention. Accordingly, the following preferred embodiment of the invention is set forth without any loss of generality to, and without imposing limitations upon, the claimed invention.

According to an aspect of the present invention, an interactive graphical user interface such as RECALL™ GUI 52 in FIGS. 5-7 is provided to a number of client machines, e.g., Co11-1N. The RECALL™ GUI 52 has a canvas 51 that allows one or more users, e.g., C11-1N, C21-2N of FIGS. 14-15, to draw or create freehand sketch entities. In the simplest case, a sketch entity consists of a line, which may be straight or curved. A basic sketch entity is created as an independent element of a more complex freehand drawing and/or to annotate, e.g., encircle or underline, a feature of an image displayed in the background of canvas 51. FIGS. 1-2 show exemplary basic and complex sketch entities, respectively. The drawing process is captured in a real time manner such that simultaneously captured multimedia/multimodal interaction information can be precisely correlated.

The real time capture of the sketch entity's creation process is enabled by timestamps Tst11-1N, Tst21-2N (see FIGS. 3, 4). Timestamps Tst11-1N, Tst21-2N have a clock frequency CLF (see FIG. 3) that may be defined by a client machine's operating system. Alternatively, CLF may be a parameter uniformly defined for all client machines. The clock frequency CLF is processed as a function of a computer's internal clock and is preferably constant.

5

The creation process of a sketch entity commences with an initiation event (e.g., **IE10-1N** of FIG. 3 or **IE20-1N** of FIG. 4). The initiation event may be triggered by, for instance, the down click of a mouse button at the time, when the cursor is within the canvas or drawing area **51** of the RECALL™ GUI **52** (see FIGS. 5-7). Depending on the hardware used to
10 create the drawing, the initiation event may also be triggered by the contacting of a drawing pin or pen with the surface of a touch screen or an activation click of a specified button of a digitizer board. In other words, the initiation event **IE10-1N**, **IE20-1N** may be any interaction of the user with any kind of input device that is feasible to recognize a predetermined initiation command. This applies also to a voice recognition system that is
15 utilized to recognize verbal commands as a means to initiate predetermined functions of the present invention. The voice recognition system may reside in a RECALL™ server or in the client machine.

The creation of the sketch entity is completed when the client triggers a termination event
20 (e.g., **TE10-1N** of FIG. 3 or **TE20-1N** of FIG. 4). The termination event may be triggered by, for instance, the release of a depressed mouse button. Depending on the hardware employed, the termination event may also be the removal of a contacting drawing pin or pen from the surface of a touch screen or the selection of a specified button of a digitizer board. In other words, the termination event **TE10-1N**, **TE20-1N** may be any interaction of the user with
25 any kind of input device that is feasible to recognize a predetermined termination command. This applies also to a voice recognition system that is utilized to recognize verbal commands

5 as a means to initiate predetermined functions of the present invention. The voice recognition system may reside anywhere accessible by the client machine.

The initiation event and the termination event define the temporal boundary condition to combine a number of drawn line segments into a sketch entity. This definition is applied in a
10 basic and an advanced form with the result of sketch entities with varying complexities.

FIG. 1 shows an example of a basic sketch entity. In correspondence with the initiation event **IE10-1N** of FIG. 3, the drawing of the curve **2** begins at the initiation point **4** and ends at the termination point **5**. The client user's drawing movements are captured in sequence, each
15 corresponding to the clock frequency **CLF** of the time stamps **Tst11-1N** of FIG. 3. As a result, a progressive number of points **6** are created and are connected by line segments **3**.

After the curve **2** is created, the RECALL™ system analyzes the numeric values of the coordinates of points **6**. During this analysis, the extreme values of the x and y coordinates
20 are recognized. These extreme values are utilized by the system to create a boundary as indicated by a dashed box **1**. The boundary **1** defines a sketch entity and serves as a dummy object, which is utilized during the creating, editing, viewing and replaying of a RECALL™ session and which is hereinafter interchangeably referred to as a "sketch object".

25 The clock frequency **CLF** defines, in combination with the drawing speed, the resolution of the curve **2**. In other words, the faster the drawing speed for a given clock frequency **CLF** the longer the distance between individual points **6**. The clock frequency **CLF** is adjusted to a

5 feasible level that balances the average drawing speed at which client users create the sketch entities with a minimal required curve resolution.

FIG. 2 shows an example of an advanced sketch entity. As illustrated in FIG. 2, the system disclosed herein advantageously provides the possibility of creating advanced sketch entities
10 that consist of a number of combined curves **22a-d**. Freehand drawings are typically created with a certain inaccuracy. To allow an automated combining of inaccurately drawn curves **22a-d**, the system of the present invention assigns proximity areas **26a-d** to the points **6**. The proximity areas **26a-d** are predetermined areas surrounding the points **6**. The aerial extension of the proximity areas **26a-d** may be defined in a vector format or a coordinate format.

15

Proximity areas **26a-d** are recognized in correlation to the curves **22a-d**. As a result, proximity areas **26a-d** that overlap with each other and that do not belong to the same curves **22a-d** trigger an automated combining of the correlated curves **22a-d**. The size of the proximity areas **26a-d** is defined in correlation to the maximal space between the points **6**
20 such that a closed area in the vicinity of the curves **22a-d** is covered by the proximity areas **26a-d**. The boundary boxes **21a-d** may be combined into one boundary box **21e**, i.e., one sketch object, or remain as separate and independent dummy objects.

The combining function may be activated as part of the system setup and/or individually by
25 assigning the initiation event to two separate initiation commands. For example, in case of a mouse, down click the right mouse button triggers an initiation event with combining function and down click the left mouse button triggers an initiation event without combining

5 function. As one skilled in the art will appreciate, the dual assignment of initiation commands for initiation events may be applied to any feasible input device, including a voice recognition system.

The system may further provide automated geometric feature recognition to correlate
10 standardized geometric elements to the freehand drawn curves. During the creation of complex freehand drawings, which may consist of a number of basic and/or advanced sketch entities, it is desirable to replace inaccurate geometric elements with computer generated accurate geometric elements. A computer generated accurate geometric element may for instance be:

- 15 1) a straight line replacing a curve within a predetermined maximal curvature;
- 2) a horizontal line replacing a curves within a predetermined maximal aberration, deviating in y-direction relative to the initiation point;
- 3) a vertical line replacing a curve within a predetermined maximal aberration, deviating in x-direction relative to the initiation point; or
- 20 4) an arc replacing a curve within a predetermined maximal curvature aberration over its length.

The automated geometric feature recognition may be extended to recognize any free hand drawn geometric form and replace it with computer generated accurate geometric elements.

25 The automated feature recognition may be activated during the setup of the system or it may be independently activated with a feature recognition command. The feature recognition command can be incorporated, for instance, as the handling variation of the input device. In

5 case of a mouse as the input device, the handling variation may be a single down click for an initiation command without feature recognition and a double click for an initiation command including feature recognition.

During the creation of basic and/or advanced sketch entities, associated multimedia
10 information can be captured in addition to the sketching activities. For example, FIGS. 3-4 show that video signal, audio signals, and sketch activities are captured simultaneously in a RECALL™ session.

In FIG. 3, the top vertical axis **V** corresponds to the signal density of the video signal **V_i**, the
15 middle vertical axis **A** corresponds to the acoustic level of the audio signals **A10-1N**, and the bottom vertical axis **SK** corresponds to the drawing path during the creation of the curves **2**. Hence, the incline angle of the sketch activities **SK10-1N** corresponds to the drawing speed at which curve **2** is created. The horizontal axis of the top, middle and bottom section represent the elapsed time. That is, the vertical raster lines that cover the top, middle and
20 bottom section represent the time stamps **Tst11-1N**. The spacing between the vertical raster lines represents the clock frequency **CLF**.

In the creation and/or editing mode, the system continuously captures audio and video signals in addition to the sketching activities. The system assigns the timestamps **Tst11-1N** to the
25 sketching activities and simultaneously to the captured audio and video. The audio signals **A10-1N** may be interrupted by silence periods **AS**. In some embodiments, the audio signals

- 5 **A10-1N** represent verbal information provided by the users, in which case, silence periods **AS** separate blocks of coherent verbal information.

The video signal **Vi** may be a consistent stream of video data that correspond in size and structure to the image resolution, the color mode, the compression ratio and the frames per
10 time unit. The video signal may be a sequence of still images at a rate that the still images are recognized as still images or that they combine in a viewer's mind to a continuous flow.

In addition to the creation/editing mode, the system of the present invention provides a replay mode and a viewing mode. In the replay mode, a selected document can be replayed such
15 that the individual sketch entities are automatically recreated in the drawing area or canvas **51**. The automatic recreation, i.e., replay, is performed in a chronological manner. The corresponding audio signals **A10-1N** and video signal **Vi** are replayed synchronously together with the replay of individual sketch entities.

- 20 In the viewing mode, a selected RECALL™ session document can be displayed with all sketch entities. A user may select one of the sketch entities displayed to begin replay. Alternatively, the user may select two or more individual sketch entities. In this case, a replay initiation routine analyzes all timestamps **Tst11-1N** correlated to the selected sketch entities and determines the earliest one. The detected earliest time stamp is taken by the system to
25 define a common starting moment for the video signal **Vi** and for the audio signals **A10-1N** respectively the silence periods **AS**. The system continuously provides the correlated audio and video data until the user makes the next selection of one or more sketch entities. At that

5 moment, the replay initiation routine is initiated again. Optionally, the audio and video can be turned off, paused, or terminated by any feasible means.

The selection process is defined by the system preferably in a form of a selection rectangle. The selection rectangle is to be created by the user by indicating two diagonal selection
10 points within the drawing area **51**, also known as drag-select. The selection rectangle selects the sketch entities by surrounding and/or intersecting with their correlated dummy objects defined by the corresponding boundary boxes described before.

In some embodiments, the selection process is performed by initiating a selection command
15 when the cursor is placed by the user/client within one of a plurality of proximity areas. By doing so, the client user is able to distinctively select singular sketch entities. This is particularly useful when there are high densities of individual sketch entities within the drawing area **51**.

20 FIG. 4 illustrates an advanced procedure captures sketch activities and associated media information to provide confined media information correlated to one or more selected sketch entities. Elements of FIG. 4 mainly correspond to those of FIG. 3. For example, timestamps **Tst21-2N** are comparable to timestamps **Tst11-1N**, initiation events **IE20-2N** are comparable to initiation events **IE10-1N**, termination events **TE20-2N** are comparable to
25 termination events **TE10-1N**, audio signals **A20-2N** are comparable to audio signals **A10-1N**, sketch activity paths **SK20-2N** are comparable to sketch activities **SK10-1N**, etc. FIG. 4 introduces an audio switching level shown in the middle section with the horizontal line **SL**.

5

Block elements of media information are provided during the advanced procedure by recognizing only audio signals **A20-2N** that are above the audio switching level **SL**. During the creation of the sketch entities, the system captures audio signals **A20-2N** between the audio initiation moments **AI1-N** and the audio termination moments **AT1-N**, respectively.

10

The audio initiation moments **AI1-N** and the audio termination moments **AT1-N** preferably share the same switching level. Alternatively, the audio initiation moments **AI1-N** and the audio termination moments **AT1-N** are triggered at different switching levels.

15

In an audio assigning procedure, the system assigns the audio initiation moments **AI1-N** and the audio termination moments **AT1-N** to the closest of the time stamps **Tst21-2N**. These times stamps **Tst21-2N** are utilized to cut the corresponding video sequences **V20-2N** out of the video signal **Vi** and to assign them to the correlated audio signals **A20-2N**.

20

The creation of sketch entities during the advanced procedure with reference to FIG. 4 is comparable to the creation of sketch entities during the basic procedure as described before with reference to FIG. 3

25

After the multimedia blocks are created, the system performs a block assigning procedure to assign the multimedia blocks to the correlated sketch entity in dependence on their time relation. Time relations include, for instance:

- 1) the sketch entity fully overlapping a multimedia block;

- 5 2) the multimedia block fully overlapping a sketch entity;
- 3) the initiation event **IE20** following the audio initiation moment **AI1** and the termination event **TE20** following the audio termination moment **AT1**;
- 4) the audio initiation moment **AI3** following the initiation event **IE22** and the audio termination moment **AT3** following the termination event **TE22**; and
- 10 5) the initiation event **IE24**, **IE2N** and/or the termination event **TE24**, **T2N** being below a minimal time span respectively below a minimal number of time stamps to the audio initiation moment **AIN** and/or the audio termination moment **ATN**.

The audio assigning procedure and the block assigning procedure may be performed with an
15 approximation algorithm provided by the system either simultaneously at the time the creation mode respectively the editing mode is activated, or after the creation mode respectively the editing mode is terminated.

During the viewing mode, the advanced procedure allows the user or users to selectively
20 review the multimedia blocks correlated to the selected sketch entity. The system provides the user with an optional predetermined audio and/or video signature to inform him/her at the end of the correlated multimedia block. Hence, the advanced procedure prevents the user from accidentally or unnecessarily seeing or hearing multimedia information unrelated to the selected sketch entity, avoiding information overload.

25

5 To provide the user with additional administrative information, the system optionally displays the individual sketch elements in varying styles. The administrative information includes, for instance:

- 1) user identification correlated to individual sketch entities of a collaboratively created document;
- 10 2) information about available multimedia blocks for individual sketch entities contained in a document; and
- 3) chronological creation of the sketch entities contained in a document.

FIGS. 5, 6 and 7 illustrate graphical coding of sketch entities described above and exemplify
15 the interactive graphical user interface 52.

In FIG. 5, the sketch entities 53, 54, 55 are shown with first graphical codes to mark them according to their creator's user (client) identification. In the example of FIG. 5, the graphical codes are varying line fonts. Graphical codes may be of any color, shape, symbolic
20 contents and/or dynamic respectively static luminescence variations. In an optional first window 56, a list 57 of collaborating clients/participating users is displayed together with the assigned graphical codes.

In FIG. 6, the sketch entities 63 and 64 are shown with second graphical codes to mark them
25 in case multimedia blocks are available. In the example of FIG. 6, the graphical codes are varying line fonts. Graphical codes may be of any color, shape, symbolic contents and/or dynamic respectively static luminescence variations. In an optional second window 66, a

5 nomenclature 67 is displayed together with the assigned graphical codes. The second graphical codes may also be applied during the viewing mode to dynamically highlight the sketch entity, whose multimedia block is replayed..

10 In FIG. 7, the sketch entities 73-76 are shown with third graphical codes to mark them according to their creation chronology. In the example of FIG. 7, the graphical codes are varying line fonts. Graphical codes may be of any color, shape, symbolic contents and/or dynamic respectively static luminescence variations. In an optional third window 78, a nomenclature 77 of the sketch entities is displayed together with the chronologically applied third graphical codes. The third graphical codes may be preferably designed with a fluent transition such that the chronology of the creation process can be easily recognized. Fluent transitions include, for instance:

- 1) the graduate change in the colors corresponding to the color spectrum; and
- 2) the continuous dilution of dotted lines.

20 The system accepts and/or provides a variety of background images that may be displayed in the create/edit/view/replay area/window/frame/canvas 51. Background images may be imported at the beginning and/or at any time during the creation of a new document, i.e., they may be laid behind an existing creation of sketch entities. Background images are preferably pictographic images like, for instance:

- 25
- 1) photographs;
 - 2) scans of graphics and/or blueprints;
 - 3) scans of text;

- 5 4) snapshots of videos;
- 5) computer assisted drawings (CAD); or
- 6) other computer-generated graphics or images.

Alternatively, the system may advantageously utilize the client computer's video capturing
10 capability to retrieve snapshots of the displayed video and to provide the snapshots as
background images. The snapshot retrieval function is preferably activated during the
creation mode. The snapshot is taken with a snapshot capturing command issued by a client
user during the real time display of the displayed video. A snapshot capturing command may
be, for instance, a mouse click at the moment the cursor is placed within the video display
15 screen, e.g., **59A**, although various implementations are possible.

The snapshot retrieval function allows multiple users **C11-1N**, **C21-2N** to comment a
captured video essentially simultaneously in real time. Hence, the snapshot retrieval function
is particularly feasible to combine a live visual experience with a documentation procedure.
20 Applications for the snapshot retrieval function are numerous, for instance, inspection of
construction sites.

FIGS. **5-7** further show the optional video display screen **59A** and the optional audio control
screen **59B**. Video display screen **59A** and the audio control screen **59B** are conventionally
25 provided by the client machine's operating system. Alternatively, the video display screen
59A and/or the audio control screen **59B** may also be provided by the RECALL™ system.
Although screens **59A** and **59B** can be respectively integrated into the RECALL™ GUI **52** as

5 separate frames or windows with independent control functions, as will be described later with reference to FIG. 10, the RECALL™ system preferably embeds a media player capable of recording and controlling audio playback (e.g., play, pause, stop, forward, reverse, etc.).

Referring to FIG. 8, the RECALL™ system comprises the following modules:

- 10 1. Recognition module **810** – recognizes words or phrases from an audio file **811** created during a RECALL™ session and stores the recognized occurrences and corresponding timestamps in text format **830**. The recognition module includes a V2T engine **812** that takes the voice/audio file **811** and runs it through a voice to text (V2T) transformation. The V2T engine **812** can be a standard speech recognition software package with
15 grammar and vocabulary, e.g., Naturally Speaking, Via Voice, MS Speech recognition engine. The recognition module **810** is further explained below with reference to FIG. 9.
2. V2TS replay module **820** – presents the recognized words and phrases and text in sync with the captured sketch and audio/video, thus enabling a real-time, streamed, and
20 synchronized replay of the session, including the drawing movements and the audio stream/voice. The V2Ts replay module **820** is further explained below with reference to FIGS. 10-12.

Recognition module

For the purpose of demonstrating an implementation of the present invention, the recognition
25 module integrates a standard speech recognition engine and speech recognition software development kit (SDK). In a specific example, the recognition module utilizes the NaturallySpeaking® engine and the NaturallySpeaking SDK from Dragon System, Inc., and

5 the Microsoft® Speech SDK in VC++. One skilled in the art will appreciate that any standard speech recognition engine and speech recognition SDK can be implemented. For effective recognition, the integrated V2T engine should have some trained user profiles for different speakers.

10 Referring to FIG. 9, the recognition module takes as input the project name of the RECALL™ session and the user whose data it should use to perform the recognition. Next, the recognition module converts the audio file corresponding to the project, e.g., *projectname.asf*, into a format recognizable to the V2T engine.

15 The V2T engine is initialized with the user profile and the converted audio file and starts transcribing thereafter. A Notify sink is created to receive notifications about events. Every time the engine identifies a phrase, it records the phrase and a timestamp in a text file, e.g., *<projectname>sp.txt*, under a designated directory, e.g., *<projectname>* directory. At the end it records the start and end of file timestamps. All timestamps are in bytes that the sound card
20 processed by the time this event happened.

V2TS Replay Module

A. Timestamp Conversion

To achieve synchronization, all the different streams of data should be played in a manner
25 that minimizes the discrepancy between the times at which concurrent events in each of the streams occurred. Thus, the timestamp information for all the streams is first translated into a common time base. The absolute system clock timestamp, with the time instant when a

5 RECALL™ session starts set to zero, serves as the common time base. Each sketch object is encoded with the system clock timestamp during the session production phase.

To convert each sketch object's timestamp into the common time base, the V2TS replay module subtracts the system clock timestamp for the instant the session starts, i.e.,

10 sketch object timestamp = raw sketch object timestamp – session start timestamp.

To convert the audio system time coordinates, the V2TS replay module multiplies the system clock timestamp obtained from the audio player, e.g., Netshow Encoder/Windows Media Player, and converts it into milliseconds. This gives the common base timestamp for the
15 audio, i.e.,

audio timestamp = raw audio timestamp * 1000.

The conversion mechanism for the transcribed data uses a slightly more involved algorithm and is a distinguishing component of the RECALL™ system. As describe before, the
20 RECALL™ session start and end timestamps are stored in byte format for the transcribed data by the recognition module, or more specifically, by the V2T engine while processing the captured audio data. On the other hand, the RECALL™ session start and end times are stored in system clock format during the production phase of the session. Thus, for a recognized word/phrase of the transcribed data, the corresponding system clock time can be found by
25 scaling the raw byte data by a factor that is determined by the ratio of the time duration of the session in system clock and the time duration in bytes. That is,

transcribed data timestamp = (Tr*Ds/Dr) + Tsst, where

- 5 Tr = raw transcribed data timestamp – raw start time
- Ds = system clock session end time – system clock session start time
- Dr = raw end time – raw start time
- $Tsst$ = system clock applet start time.

- 10 The $Tsst$ term is later subtracted from the calculated value to obtain the common base timestamp.

Based on the above-described functionalities, a keyword search is implemented to identify all the keyword instances in a particular session, i.e.,

- 15 keyword timestamp = system clock keyword timestamp – session start timestamp.

The keyword search functionality is explained in more detail later with reference to FIG. 10.

B. Programming Language and Data Structure

- In an embodiment, the programming for the synchronized replay of the RECALL™ session
20 is done in Java 1.3. Important Java classes and data structures are listed below.

1. *Replay Applet*: The main program controlling the replay session through a hypertext markup language (HTML) file. **[Will other markup language, e.g., XML, be possible?]**
2. *Storage Table*: The table storing all the sketch objects for a single RECALL™ page.
3. *TextIndex*: The array storing all the recognized phrases in the session.
- 25 4. *ReplayFrame*: The frame on which sketches are displayed.
5. *TextReplayFrame* : The frame on which recognized phrases are displayed.
6. *ReplayControl*: The thread coordinating audio and sketch.

- 5 7. *TextReplayControl*: The thread coordinating text display with audio and sketch.
8. *RecallObject*: The data structure incorporating information about a single sketch object.
9. *Phrase*: The data structure incorporating information about a single recognized phrase.

In an embodiment, the RECALL™ system may include a RECALL™ working directory
10 containing the following files:

1. *Projectname_x.html* : The HTML file to display page x of a RECALL™ session;
2. *Projectname_x.mmr*: The data file storing the storage table for page x of the session,
generated in the production phase thereof; and
3. *Projectnamesp.txt*: The data file storing the recognized phrases for the entire RECALL™
15 session, generated from the recognition module.

The RECALL™ system may further include an audio file directory, <asfroot>, containing
the audio file, *projectname.asf*, for the entire session.

20 C. Synchronization and Replay Scenarios

In an embodiment, the entire RECALL™ session is represented as a series of thumbnails for
each new page in the session. One can browse through the series of thumbnails and select a
desired page for replay. Below describes with details of implementation a scenario 1000
where a particular page is selected for replay.

25

Referring to FIG. 10, a particular RECALL™ session page is presented as a webpage 1010
with the *Replay Applet* running in the background. When the applet is started, it instantiates

5 the media player **1040** with a link to the audio file to be loaded and the time to start from for that particular page. It also opens up a *ReplayFrame* **1020** which will display all the sketches **SO1-SON** made during the session and a *TextReplayFrame* **1030** which will display all the recognized keywords **1032** spoken during the session.

10 As illustrated in FIG. 10, the keyword search functionality enables a user to search/select a keyword “wingspan” via an input box **1035**. The session then begins to replay in the *ReplayFrame* **1020** from the point when the latest sketch object was drawn before the corresponding keyword “wingspan” was spoken. The *ReplayFrame* **1020** may have several functionality buttons **1025**, e.g., show, play, pause, resume, etc. The captured sketches or
15 sketch objects **SO1-SON** are replayed in sync with the associated audio signals captured essentially simultaneously therewith. Transcribed text corresponding to the audio can also be synchronously replayed in the *TextReplayFrame* **1030**.

The V2TS replay module hierarchy is illustrated in FIG. 11. In addition to the *ReplayFrame*
20 **1020** and the *TextReplayFrame* **1030**, the applet also reads in the RECALL™ data file (*projectname_x.mmr*) into a *Storage Table* and the recognized phrases file (*projectnamesp.txt*) into a *TextIndex* Object. *TextIndex* is basically a vector of *Phrase* objects with each phrase corresponding to a recognized phrase in the text file along with the start times and end times of the session in bytes as well as absolute time format to be used for time
25 conversion.

5 When reading in a *Phrase*, the initialization algorithm also finds the corresponding page, the number and time of the nearest sketch object that was sketched just before the phrase was spoken and stores it as a part of the information encoded in the *Phrase* data structure. For this purpose, it uses the timestamp conversion algorithm as described above. This information is also used by the keyword search functionality.

10

Now we have an active audio file, a table with all the sketch objects and corresponding timestamps and page numbers, and a vector of recognized phrases with corresponding timestamps, nearest object number and page number.

15 In the V2TS replay module, multiple threads control the simultaneous synchronized replay of audio, sketches, and transcribed keywords. More specifically, the *ReplayControl* thread controls the drawing of the sketch and the *TextControl* thread controls the display of the keywords. FIG. 12 illustrates the V2TS replay module control flow according to an aspect of the present invention.

20

The *ReplayControl* thread keeps polling the audio player 1040 for the audio timestamp at equal time intervals. This audio timestamp is converted to the common time base as described before. Then, the table of sketch objects SO1-SON is parsed, their system clock coordinates converted to the common base timestamp and compared with the audio common
25 base timestamp. If the sketch object occurred before the current audio timestamp, it is drawn onto the *ReplayFrame* 1020. The *ReplayControl* thread repeatedly polls the audio player

5 **1040** for timestamps and updates the sketch objects **SO1-SON** on the *ReplayFrame 1020* on the basis of the received timestamp.

The *ReplayControl* thread also calls the *TextControl* thread to perform this same comparison with the audio timestamp. The *TextControl* thread parses through the list of keywords in the
10 *TextIndex* and translates the raw timestamp to common base timestamp and then compares it to the audio timestamp. If the keyword timestamp is lower, the keyword is displayed in the *TextReplayFrame 1030*.

The latest keyword and the latest sketch object drawn are stored so that parsing and
15 redrawing all the previously occurring keywords is not required. As such, only new objects and keywords need to be processed. This process is repeated until all sketch objects are drawn.

D. Keyword Search and Selection Facility

20 The V2TS replay module also includes a keyword search and selection facility so a particular keyword in the transcription can be searched. The session can then be synchronously replayed from the time when the word was spoken.

According to an aspect of the invention, when a keyword is entered, e.g., via the input box
25 **1035** in the *TextReplayFrame 1030*, the system parses through the list of recognized keywords and phrases in *TextIndex* to identify the selected keyword. If the system is able to find a hit, it retrieves the concerned keyword's page number, nearest sketch object number

5 and sketch object time that was stored when the *Phrase* corresponding to the keyword was being initialized. Currently, the first hit is considered in cases where there are multiple hits.

The V2TS replay module then resets the *ReplayFrame* to reference the *mmr* file corresponding to the particular page number. It also resets the *TextReplayFrame*,
10 *ReplayControl* and *TextControl* accordingly to begin sketching and text display from that retrieved object number, onwards also adjust the audio player position to the timestamp of the latest sketch object.

As one skilled in the art will appreciate, it is within the scope of the present invention to
15 implement the V2TS replay module so that it jumps directly to the instant when the keyword was spoken. However, setting the session to begin replay from the latest sketch drawn before the keyword was spoken provides the user with more context in which the keyword was used.

20 On the other hand, the V2TS replay module also enables the user to select an item in the sketch and replay from there. More specifically, when a sketch object is selected as the starting point for replay, the V2TS replay module starts playing from the selected object and also adjusts the audio player to start playing corresponding audio from that time. This is described in more detail in the above-referenced co-pending U.S. patent application, now
25 allowed.

In essence, the present invention enables a user to decide and select when, how much, and

5 what captured content rich multimedia information is replayed. To begin replaying the session, the user can select a sketch object or a keyword. The session starts replaying from the selected sketch object or the latest sketch object corresponding to the selected keyword. The sketch objects are re-drawn on an interactive graphical user interface in real time in sync with the audio player, that start playing the voice stream from that time, and with the text
10 replay, that prints in the text window what is said. With the synchronized text replay, the present invention can be surprisingly effective for scenarios involving, for instance, (1) a very noisy environment, or (2) hearing impaired users.

FIG. 13 is a snapshot of an exemplary interactive RECALL™ GUI 1300 having a color
15 pallet 1315, a plurality of functionality buttons 1325, and a canvas or drawing area 1310 onto which a user can sketch free hand drawings or writings. In this example, a 2D CAD object is imported as a background image on the canvas 1310. The user annotates the imported image with sketch objects SK1-SKN.

20 Several functionalities of the RECALL™ GUI 1300 are described below. One skilled in the programming art should have no problem implementing or adding other functionalities.

1. **Undo:** removes the last sketched object from the canvas.
2. **ClearSketch:** removes all objects sketched on the current canvas. ClearSketch does not remove the background image from the canvas.
- 25 3. **LoadImage:** allows the user to load a background image onto the canvas. Upon selection, it opens a file dialog box to allow the user to retrieve any desired image.
4. **ClearImage:** removes the background image in the current canvas. The sketched objects

5 remain untouched.

5. **LoadPPT:** allows the user to load a Microsoft® PowerPoint® presentation. Upon selection, it opens a file dialog box to allow the user to choose a presentation. The slides of the chosen presentation are displayed on a new window in the form of, e.g., thumbnail images, and may be chosen as backgrounds on the canvas for further mark-up and
10 annotation.

6. **2D and 3D:** respectively places a 2 dimensional and a 3 dimensional grid on the canvas to assist the user sketching.

7. **SubPage:** stores the current canvas as an adjunct to the current page the user is working on. Contents of a subpage can be imported onto the canvas using **Merge or Select**
15 functionalities described below, thus emulating the multiple tracing papers metaphor familiar to designers.

8. **Merge:** allows the user to import sketched objects stored as subpages. The merge functionality is toggled on and off with the selection of the merge button. For example, a first click on the merge button activates the merge functionality. Thereafter, selecting any
20 subpage icon would cause its sketched objects to be imported onto the canvas. A second click on the merge button deactivates it.

9. **Select:** allows the user to import the sketched objects of any one subpage onto the canvas. The subpage is selected by selecting, e.g., clicking, its icon.

10. **Trace and Overlay:** the **Trace** and **Overlay** functionalities work in tandem. On
25 selecting/clicking the trace button, the trace mode is activated, again emulating the tracing metaphor familiar to CAD/graphic designers or technical drawing specialists. Any sketched object now drawn on the canvas is saved by the system in a buffer. The trace

5 mode is deactivated by toggling/clicking on the trace button again. The **Overlay** functionality is used to place the contents of the buffer onto the current canvas.

11. **Screenshot and Placeshot:** The **Screenshot** functionality takes a picture of the current screen content. The **Placeshot** functionality places that picture on the current canvas as background.

10

FIGS. **14A** and **15** show two different system architectures in which the RECALL™ system may be embodied. Both system architectures can be implemented in a distributed network such as an intranet or the Internet. FIG. **14A** shows the preferred embodiment of a centralistic system architecture incorporated in a web page distribution system **1400**. A RECALL™ Web
15 Server **S1** operates a web site and is accessible by a number of client users **C11-1N** via their corresponding client machines **Co11-1N**.

FIG. **14B** illustrates an aspect of FIG. **14A** in which a RECALL™ system comprises an audio/video capture means **1401**, an audio/video encoding means **1403**, a sketch capture
20 means **1402**, and a sketch encoding means **1404**. Sketches, drawing movements, and associated multimedia/multimodal interaction information are captured, encoded, and stored in a storage means **1405**, which is maintained by the RECALL™ Web Server **S1**.

As an example, a user **C11** employs a computer **Co11** to communicate with the RECALL™
25 Web Server **S1**. The computer **Co11** may be operatively coupled to the audio/video capture means **1401**, e.g., a video camcorder, and the sketch capture means **1402**, e.g., a digitizer board. After a login event that verifies user **C11**'s identification and/or authorization, user

5 **C11** is able to utilize the interactive RECALL™ GUI and the underlying RECALL™ software to create, edit, replay and view sketches and corresponding drawing movements, text, audio, video, or other multimedia/multimodal interaction information. The software components of the interactive RECALL™ GUI can be appreciably implemented in the RECALL™ Web Server **S1**, in the computer **Co11**, or suitably augmented. [NOTE: Please
10 correct or verify. Thanks.]

The RECALL™ software enables the client machine **Co11** to create and store work files, i.e., script logs **Sc11-1N**. The script logs **Sc11-1N** contain all data gathered during the session production phase. The computer **Co11** is in bidirectional communication with the
15 server **S1**, which stores the script log **Sc11** in a permanent log **PL11**.

The permanent log **PL11** is the computer readable representation of the creation process of a RECALL™ document. That is, each permanent log is a detailed digital file record of sketching activities captured in a RECALL™ session. It is continuously updated with all
20 scrip logs **Sc11-Sc1N** that are created on the client machines **Co11-Co1N**. A database **Db10** maintained by the server **S1** stores the permanent logs **PL11-1N** of a number of documents created and edited by the users **C11-C1N**. Hence, the server **S1** is the central storing and redistribution site for all RECALL™ documents created and edited by the users **C11-C1N**.

25 When the user **C11** wants to retrieve a RECALL™ session for viewing or editing, he/she initiates a retrieval request command via the interactive RECALL™ GUI at the client

5 machine **Co11**. The retrieval request command is communicated via appropriate communication means to the server **S1**.

The requested RECALLTM session document is identified, selected, and transmitted in the form of the permanent log **PL11** to the client machine **Co11** and becomes accessible for
10 replay, editing and viewing. All changes are documented in an additional script log **Sc11-Scl1N** that is sent back to the server **S1**, where the newly created script log **Sc11-Scl1N** is added to the already existing permanent log. The script logs **Sc11-Scl1N** may be transmitted to the server **S1** continuously during the session production phase.

15 Erasing activity may be captured as a regular part of the creation process and/or subsequently removed from the script log and the permanent log. The RECALLTM system further provides a rewind function to allow the user to rewind and erase the captured creation process up to a chosen moment and to start over again.

20 The centralistic system architecture may be applied to any form of network where the users **C11-C1N** can simply logon to the server **S1** at any time. Further, the centralistic system architecture may consist of a number of servers **S1** that compare and update the context of their respective database **Db10** independent of the operation of the client machines **Co11-Co1N**.

25

Alternatively, the RECALLTM system implements an equalized system architecture **1500** as shown in FIG. **15**. In this case, a number of users **C21-C2N** independently operate their

5 respective client machines **Co21-Co2N**, each of which independently maintains a respective database **Db21-Db2N**. The databases **Db21-Db2N** are stored on a first direct access storage device (FDASD) and contain a number of permanent logs **PL21-PL2N** comparable to permanent logs **PL11-1N**. The RECALL™ software described above resides in a second direct access storing device (SDASD) accessible to the client machines **Co21-Co2N**.

10

The storage medium of the SDASD and/or the FDASD may be a removable storage medium like, for instance, a CD or it may be incorporated in the computers **Co21-Co2N** as it is the case, for instance, in a hard disk drive.

15 Whenever a computer **Co21** establishes a communication connection to other computers **Co22-Co2N**, the clocks of each computer are verified for synchronicity and eventual synchronized. Then, the databases **Db21-Db2N** are automatically compared and updated. The equalized system architecture allows users **C21-C2N** to operate the RECALL™ system independently, in spite of an available wired or wireless network communication connection.

20

The RECALL™ system architecture is not limited to any particular network communication framework. The centralistic and the equalized system architectures, which may be combined temporarily or in any other feasible scheme, can be appreciably implemented with any suitable network communication technology that offers real time or essentially real time data
25 exchange. The techniques necessary to do this are known to those skilled in the art.

- 5 The functional components of the RECALL™ system are written in a commonly known computer language, i.e., Java. Various software development systems provide the tools to create the computer readable code of the RECALL™ system in accordance to the possibilities and needs of the used operating system.
- 10 The databases **Db10, Db21-Db2N** and/or the RECALL™ software may be installable on the computers **Co11-Co1N, Co21-Co2N** in the form of:
- 1) a downloadable file accessible via a web page;
 - 2) a self extracting file attached or part of an email message;
 - 3) incorporated in a web browser;
 - 15 4) incorporated in an operating system; or
 - 5) a computer readable file stored on a tangible medium like for instance a Compact Disk.

In conclusion, the RECALL™ system disclosed herein provides content and context (the
20 graphic segments synchronized with associated audio, text, and video) driven capture and replay. A user is able to directly manipulating content in essentially real time. That is, the user can select any graphic segment, i.e., drawing movements, in the sketch and replay through real-time streaming audio-video-graphics from that point on. This content and context driven capture and replay approach allows for future intelligent indexing of content
25 of RECALL™ sessions that reside on a server database.

5 Preferably, the invention is implemented in a client-server architecture that provides a real time streaming of content from an Internet server, allowing multiple users to replay RECALL™ sessions on any Internet-enabled device. Concurrent and dynamic multiple content streaming of the same content to a number of users is also possible. In other words, the RECALL™ sessions can be distributed to any number of users through real time
10 streaming of audio-video-sketch and does not require the user to record the session for additional replays, thereby enabling efficient information/knowledge/content re-use.

The present invention advantageously provides content-rich multimedia recall, knowledge reuse, synchronous playback, and multimodal interactivity, further enhancing existing
15 interactive technologies such as videoconferencing.

As one skilled in the art will appreciate, most digital computer systems can be programmed to perform the system and method disclosed herein. To the extent that a particular computer system configuration is programmed to implement the present invention, it becomes a digital
20 computer system within the scope and spirit of the present invention. That is, once a digital computer system is programmed to perform particular functions pursuant to computer-executable instructions from program software that implements the present invention, it in effect becomes a special purpose computer particular to the present invention. The necessary programming-related techniques are well known to those skilled in the art and thus are not
25 further described herein for the sake of brevity.

5 Computer programs implementing the present invention can be distributed to users on a computer-readable medium such as floppy disk, memory module, or CD-ROM and are often copied onto a hard disk or other storage medium. When such a program of instructions is to be executed, it is usually loaded either from the distribution medium, the hard disk, or other storage medium into the random access memory of the computer, thereby configuring the
10 computer to act in accordance with the inventive method disclosed herein. All these operations are well known to those skilled in the art and thus are not further described herein. The term "computer-readable medium" encompasses distribution media, intermediate storage media, execution memory of a computer, and any other medium or device capable of storing for later reading by a computer a computer program implementing the invention disclosed
15 herein.

Although the present invention and its advantages have been described in detail, it should be understood that the present invention is not limited to or defined by what is shown or described herein. As one of ordinary skill in the art will appreciate, various changes,
20 substitutions, and alterations could be made or otherwise implemented without departing from the principles of the present invention. Accordingly, the scope of the present invention should be determined by the following claims and their legal equivalents.